

ASSEMBLY INSTRUCTION

SKU#250-464

Note: Please consult a qualified electrician if you are not certain of the installation.

CAUTION: Before starting the installation, disconnect the power by turning off the circuit breaker or by removing the fuse at the fuse box. Caulk to mounting surface at top and sides

1. Fasten mounting strap onto outlet box using 2 outlet box screws provided.
2. Screw off ring from screw collar loop on the mounting strap.
3. Screw loop down to short nipple of the fixture.
4. Using two pliers, twists open the link at the end of the chain. Hook it to loop and close the link. Weave fixture wires up through loop, through chain links, through ring, through canopy, and through mounting strap. Carefully position wires back into outlet box. Open the link at the other end of the chain. Hook whole fixture to screw collar loop and close link.
5. Connect the wire with writing on it from fixture to the black wire from supply circuit. Connect the wire without writing on it (with raised ribs) from fixture to the white wire from supply circuit. Cover connections using wire connectors provided. Tie ground wires from outlet box and from fixture to ground screw on mounting strap.
6. Place the canopy all the way to the ceiling and tighten the ring onto the screw collar loop until the canopy is firmly held against the ceiling.
7. Install the bulbs (included).
8. Place decorative pan and fixture frame over the fixture body and fasten them using the bushing. Screw the long nipple into the bushing. Place bottom cover over long nipple onto the fixture and fasten it with finial.

